



FEATURES

- Integrated with IPX600
- · Touch display
- Dedicated lines for access to and monitoring of conferences
- · Split headset support
- External loudspeaker

MLT600 Multi Line Terminal

Advanced Digital Voice Terminal

The MLT600 is an advanced digital voice terminal connected through Ethernet to the tactical router and media gateway unit (IPX600) within K-TaCS.

The MLT600 is power fed using PoE through the Ethernet interface or locally connected 12 VDC.

The MLT600 is a digital multi line voice terminal equipped with:

- Touch display for use as a standard digital voice terminal
- Dedicated line keys, configurable for subscriber facilities
- · Keys for access to conferences
- Support for split headset
- Support for footswitch (option)

The MLT600 can:

- Serve subscribers with requirements for multiple subscriber facilities in an effective way
- Handle up to ten communication lines in parallel
- Monitor up to two lines (battle circuits or radio networks) at the same time

MLT600 is typically used by Air Defence operators or in Command Posts. Easy and rapid access to critical communication lines through preconfigured keys on the MLT600 makes it possible for the operators to stay focused on their main task.

kongsberg.com 2024/06/00



MLT600 used in the advanced KONGSBERG Raytheon NASAMS Air Defence System

TECHNICAL DATA

Interfaces 1LAN

1 split headset

2 external loudspeakers

Protocols IPv4

SIP DHCP NTP

Power Supply PoE

12 VDC

Environmental Operating temp.: -30°C to +55°C

Environmental: MIL-STD-810 army ground EMC: MIL-STD 461 army Ground

Dimensions Height: 260 mm

Width: 152 mm Depth: 58 mm Weight: 1,5 kg



Application on Naval Systems



Application on Weapon Systems



Application on C5I Systems