





## The professional GNSS tracking solution

The Seatrack 320 represents the state-of-the-art in relative GNSS tracking systems combined with over 20 years of operational experience in extreme maritime environments. Utilizing the latest in GNSS technology, the Seatrack 320 transponder is tailored to applications demanding a high-end solution in reliability and accuracy. Seatrack 320 transmits data through serial interface or UHF-radio.

## **Technical specifications**

Performance

Accuracy 1 m Update rate Up to 1 Hz

**GNSS** 

GPS L1

Radio

Frequency 450 - 470 MHz
Channel separation 12.5 kHz
Transmission power 0.5 W

Typical range 15 km (line-of-sight)

I/O

UHF radio RS-232 Different connector options available.

Weight and dimensions

Diameter 150 mm Height 640 mm Weight 4.5 kg Power specifications

Supply voltage 10 - 36 VDC Mean power consumption 4 W

**Environmental specifications** 

Operating temperature  $-10 \,^{\circ}\text{C} - +55 \,^{\circ}\text{C}$ Storage temperature  $-30 \,^{\circ}\text{C} - +70 \,^{\circ}\text{C}$ Enclosure protection IP68, 10 m

Standards and regulations

Electromagnetic compatibility Compliance to EMCD,

immunity/emission IEC 60945/EN 60945

Product safety
Compliance to LVD,

Compliance to LVD, standard used

IEC 61010-1/EN 61010-1

Specifications subject to change without any further notice.