

中国船级社 CHINA CLASSIFICATION SOCIETY

证书编号/Certificate No. **BG24PTB00001 02**

型式认可证书 CERTIFICATE OF TYPE APPROVAL

兹证明本证书所述制造厂具备按照下列标准的要求生产本证书所列产品的能力和条件。

This is to certify that the manufacturer stated in the certificate meets the requirements of the standards listed below and is available with the ability and conditions to produce the products described in the certificate.

制造厂/Manufacturer

Kongsberg Maritime AS (Kongsberg)

地址/Address

Kirkegardsveien 45, P.O. Box 483, NO-3601 Kongsberg, Norway

产品名称/Product

雷达设备 Radar equipment

认可标准/Approval Standard

1. 国际海事组织海安会决议MSC. 466(101)《船载航行显示器有关航行信息显示的性能标准》(MSC. 191(79)决议)修正案

IMO MSC.466(101) Amendments To The Performance Standards For The Presentation Of Navigation-Related Information On Shipborne Navigational Displays (Resolution MSC.191(79))

2. 国际海事组织大会决议A. 694(17)《作为全球海上遇险和安全系统(遇险和安全系统)组成部分的船载无线电设备和电子助航设备的一般要求》

IMO Resolution A.694(17) General Requirements for Shipborne Radio Equipment Forming Part of the Global Maritime Distress and Safety System (GMDSS) and for Electronic Navigational Aids

3. 国际海事组织海安会决议MSC. 191 (79) 《船载航行显示器有关航行信息显示的性能标准》

IMO Resolution MSC.191(79) Performance Standards for the Presentation of Navigation-Related Information on Shipborne Navigational Displays

4. 国际海事组织海安会决议MSC. 192(79)《经修订的〈关于雷达设备性能标准的建议案〉》

IMO Resolution MSC.192(79) Adoption of the Revised Performance Standards for Radar Equipment

5. 国际海事组织大会决议Res. A. 278(VIII)《航海雷达设备控制符号》

IMO Res.A.278(VIII) Control Symbol of Navigation Radar Equipment

6. 国际海事组织大会决议Res. A. 823(19) 《船用自动雷达标绘仪性能标准(ARPAs)》

IMO Res.A.823(19)Performance Standards for Automatic Radar Plotting Aids (ARPAs)

7. 国际电讯联盟建议书ITU-R M. 1177-4(04/2011) 《对于雷达系统无用发射的测量技术》

ITU-R M.1177-4(04/2011) Techniques for Measurement of Unwanted Emissions of Radar Systems

8. IEC 62388:2021《导航和无线电设备-船用雷达-性能要求、测试方法和要求的测试结果》

IEC 62388:2021 Maritime navigation and radiocommunication equipment and systems - Shipborne radar - Performance requirements, methods of testing and required test results

9. IEC 60945:2002/COR1:2008《船用航行和无线电通信设备及系统-通用要求-试验方法和试验结果的要求》

IEC 60945:2002/COR1:2008 Maritime Navigation and Radiocommunication Equipment and Systems –General

Regarrement Methods of Testing and Required Test Results

证书有效期至/ his Gertificate is valid until

2029年07月01日/Jul. 01,2029

发证机构,中国和级社会学根办事处

签发日期 2024年12月20日

Issued by CANSCAROS of fice

Date Dec. 20,2024

本证书根据中国船级社规范和相关规定签发。所有证书页为一个整体,必须同时使用。纸质证书每页均须由本社盖章方为有效,电子证书含数字签名方为有效,本证书复印件无效。任何单位和个人均不应摘录或节选本证书的部分内容。有关方对所持证书的真实性有疑问时,可以向我社检验机构咨询。本证书见是未注明版本的规范,其(发证时)最新版本适用于本证书。

This Certificate is issued pursuant to the Rules of the Society and related regulation. All pages of the certificate are taken as a whole and are used simultaneously. No paper certificate page is valid without bearing the stamp of the Society, no electronic certificate is valid without bearing the stamp of the Society, no electronic certificate is valid without bearing the stamp of the Society, no electronic certificate is valid without bearing the authenticity of the certificate is valid. Any part of the certificate is not to be extracted or abridged by any unit or individual in any form. Related parties who are doubted about the authenticity of the certificate may inquire of the Society or its offices. For Rules with no version indication, their latest version (at the time of issuance of the certificate) applies to the this certificate.



UTN:P024-34183395

用于/Intended for

船舶/Ships

产品明细/Product Description

雷达设备/Radar Equipment (M0001)

名称/Name	属性 (值) /Value	单位/Unit
型号/Type	K-Bridge Radar & K-Bridge Radar	
至亏/Type	Standalone (SA)	
	1. K-Bridge Radar system: K-Bridge Operator	
	Station, Software Modules, Radar Interface,	
	Transceivers and Antenna Units	
系统组成/System Component	2. Bridge Radar Standalone(SA) system:	
	Bridge Radar Standalone(SA) Operator	
	Station, Software Modules, Radar Interface,	
	Transceivers and Antenna Units	
峰值功率/Peak of Output Power	Listed on the addtional pages	kW
天线长度/Length of Antenna	Listed on the addtional pages	foot
软件版本号/Software Version	9.1.x onwards	
工作	X-Brand:9.410GHz	
工作频率/Operating Frequency	S-Brand: 3. 050GHz	
最小操作显示区直径/Minimum Operation	200 250	
Display Area Diameter	320, 250	mm
是否具有自动捕获目标功能/Whether		
Includes Auto Acquisition of Targets	Yes	
Function		
是否具有试操船功能/Whether Includes	Yes	
Trial Manoeuvre Function	ies	
最少被捕获的雷达目标数/Minimum Acquired	100	pcs.
Radar Targets Capacity	100	pes.
最少被激活的AIS 目标数/Minimum Acquired	300	pcs.
Ais Targets Capacity		pes.
最少休眠AIS 目标数/Minimum Sleeping Ais	300	pcs.
Targets Capacity		pes.
罗经安全距离/Compass Safe Distance	90	cm
性能监测器型号/Performance Monitor Type	Transponder	
是否集成电子标绘(EPA)功能/Whether		
Electric Plotting Aid Function Be	Yes	
Integrated Into The Radar Equipment		
是否集成自动目标跟踪(ATA)功能/Whether		
Automatic Tracking Aid Function Be	Yes	
Integrated Into The Radar Equipment		
是否集成自动雷达标绘(ARPA)功能/Whether		
Automatic Radar Plotting Aid Function Be	Yes	
Integrated Into The Radar Equipment		
额定电压/Rated Voltage	AC230-400, DC24	V

批准的图纸/Approved Drawings

图纸批准号/ Drawings Approval No.: BG20PPP20002, NP24PPP03655

产品认可试验报告/ Approval Test Report

试验报告编号/ Test Report No.: See "Additional page"

试验报告日期/ Test Report Date:

试验单位/ Laboratory: See "Additional page" 试验单位地址/ Test Address: See "Additional page"

认可后的产品检验方式/ Method of Product Inspection after Approval

按规范认可后应进行产品检验的产品/The product should be inspected in term of the rules: 认可后的产品检验应由本社验船师根据本社规范规定按批准的产品检验计划进行检验,经检验合格后由本社颁发船 用产品证书。

After approval, product inspection should be carried out by the Surveyor of the Society in accordance with the approved product inspection scheme, and the Marine Product Certificate will be issued by the Society upon satisfactory inspection.

认可保持条件/ Maintenance Requirements of Approval

1. 型式认可后,如果产品及其重要零部件的设计、所用材料或制造方法有所改变,且影响到产品的主要特性、特征;或产品的性能指标有所更改,且超过认可的范围,则有关图纸和文件应经检验机构审批。并在检验机构认为必要时,经本社检验人员见证有关试验和进行检查,其结果应能证实仍符合认可条件。

After type approval, if there are changes to the design, materials used or manufacturing method of the product and important components and such changes affect major characteristics and properties of the product, or property indexes of the product are changed and exceed the scope of approval, related drawings and documents are to be examined and approved by the concerned survey office. Where deemed necessary by the survey office, the surveyor to the Society will go to witness relevant tests and conduct inspection and the results should be able to demonstrate compliance with the approval conditions.

2. 工厂的质量管理体系应保持有效运行,并且与认可时一致。如果质量管理体系发生改变,应经原体系认证机构审核并报本社批准。

The quality management system of the factory shall be ensure effective operation, and shall be the same as the situation of approval. If there are any changes to the quality management system, auditing of the original certification organization for quality management system and the society's approval shall be obtained.

3. 认可证书有效期内,如果出现可能导致本社取消认可的情况,工厂应及时采取有效的纠正措施。

Within the validity of the approval certificate, if cases occur that may cause the Society to withdraw the approval, the manufacturer should take corrective actions in a prompt and effective manner

4. 在认可证书有效期内,本社检验人员可在未经事先通知的情况下对工厂的产品制造过程进行审核,以验证产品的生产是否符合业经本社批准的图纸和文件。工厂应予以配合。

Within the validity of the approval certificate, the surveyor to the Society may pay unannounced audit to the manufacturing process of the product in order to confirm whether it is in compliance with the drawings and documents approved by the Society. The factory should provide an active cooperation and necessary for the surveyor.

5. 如果属于获得型式认可B模式证书,且无需颁发船用产品证书/等效证明文件的情况,证书获得者应接受本社每年一次的定期审核,定期审核日为认可证书期满之日对应的每一周年日,检查工作应在周年日的前后三个月内进行。

If belong to the situation of the product has type approval mode B certificate, and marine product certificate/equivalent document is not necessary, those who have obtained the certificate should be subject to periodical audit every year. The date of periodical audit shall be each anniversary date which corresponds to the date of expiry of the relevant certificate and the periodical audit shall be done within a time span of three months before and after the annual surveillance date.

备注/Remarks

- 1. 本证书由原型式认可证书 (No. BG19PTB00028_02) 换新并替代原证书。 This certificate is renewed from and supersedes the previous Type Approval Certificate No. BG19PTB00028 02.
- 2. Regarding other product description, please refer to "Additional pages"
- 3. The system shall be installed and tested on board according to manufacturers manuals as attached in this certificate.
- 4. 本社已审核了产品厂无石棉声明,但本社的审核不免除产品厂按照合同关系向订货方保证产品无石棉的责任。 The declaration of asbestos-free submitted by manufacturer has been reviewed by the Society. However, liability of the manufacturer to guarantee the products are asbestos-free to purchaser under contract will not be exempted.

中国船级社卑尔根办事处

CCS Bergen Office

注: 本证书含有附页, 共3页

Note: The certificate is attached with additional 3 page(s)

1.Other product description

- 1.1 Regarding the definition of K-Bridge Operator Station, K-Bridge Standalone Operator Station and Software Modules, please refer to type approval certificate BG24PTB00001 06.
- 1.2 Radar Interface Network : RIN rev A or rev C, which is only supported in combination with Northrup Grumman Sperry Marine transceivers and antenna units in an up-mast configuration
- 1.3 Ethernet switch: Moxa EDS-G509
- 1.4 The details of the Radar connected to this system are as follows:

A.Manufacturer: Northrop Grumman Sperry Marine

Name for Transceivers Units	Type	Note
X-Band Transceiver/Turning Unit(10 kW)	65910#A≠	1,2,3,6
or Transceiver/Bulkhead(10 kW)	65910A,B,E,F,G,H,L,P,T or	6
	W	
X-Band Transceiver/Turning Unit(25 kW)	65925#A≠	1,2,3,6
or Transceiver/Bulkhead(25 kW)	65925A,B,E,F,G,H,L,P,T or	6
	W	
Turning unit X-band (w/Bulkhead Tx)	65901BAR or CA≠	2,3,6
S-Band Transceiver/Turning Unit(30 kW)	65830M§R or N§≠	3,4,6
or Transceiver/Bulkhead(30 kW)	65831 A or B	6
Turning unit S-band (w/bulkheadTx)	65830B§≠or C§≠	3,4,6
Scanner Control unit S-band	65837АФ	5,6

Name for Antenna	Type	Note
Array 12' S-unit	65612A	6
Array 8' X-unit	65608A	6
Array 6' X-unit	65606A	6

Notes:

- 1. A 1st letter (#) suffix (M,N,P,T or W) is used to denominate the choice Bias limiter, Extra short pulse transmit or Additional facilities.
- 2. This item is link selectable on installation to 24 or 48 RPM antenna rotation speed.
- 3. A 3rd letter (\neq) suffix (R,T or U) is used for denote the choice of pulse and/or syncro azimuth signal.
- 4. A 2nd letter(§) suffix(E,F,G,H,J,K,L,M,P,Q,R or S) is used to denote the choice of operating voltage and 24 or 48 RPM antenna rotation speed.
- 5. A 2nd letter (Φ) suffix (B,C,E,F or H) is used to denote the choice of operating voltage and 24 or 48 RPM antenna speed.
- 6. The type number may be followed by suffix /KM.

B. Manufacturer: JAPAN RADIO CO., LTD.

Name for Transceivers Units with Antenna	Type
X-band Transceiver (10kW), 27 rpm, 6ft antenna	NKE-2103-6/KM
X-band Transceiver (25kW), 24 rpm, 9ft antenna	NKE-1125-9/KM
S-Band Transceiver (30kW), 24 rpm, 12ft antenna	NKE-1130-12S/KM
S-band Transceiver, Solid State (250W), 24 rpm, 8ft antenna	NKE-2632-8S/KM
X-band Transceiver, Solid State (600W), 24 rpm, 6ft antenna	NKE-1696-6/KM
X-band Transceiver, Solid State (600W), 24 rpm, 9ft antenna	NKE-1696-9/KM
S-band Transceiver, Solid State (250W), 48 rpm, 8ft antenna	NKE-2632-8S-H/KM

2. Approval Test reports

No.	Report No.	Report date	Lab./Test Address	Note
1	6811479	2024.08.20	Kongsberg Maritime/Norway	Renewal testing & FAT report
2	418199	2017.01.31	Kongsberg Maritime/Norway	Test report for K-Bridge & K-Nav CCRS - Clause 6
3	415226	2017.01.25	Kongsberg Maritime/Norway	K-Bridge & K-Nav Radar Type Approval Test report, IEC 62388 (2013), IEC 62288 (2014) and IEC 61162 (2010)
4	401092	2015.05.22	Kongsberg Maritime/Norway	Protocol tests on interface for K-Nav Radar
5	387381	2014.04.28	Kongsberg Maritime/Norway	RoLAN Target tracker Scenario 1 test report
6	OOBEvidenceFor 62388Ed2	2014.02.13	SPERRY MARINE BV/Netherlands	Assessment report for S- and X-band radar towards IEC62388 Ed2.0
7	393352	2014.04.25	Kongsberg Maritime/Norway	RoLAN network test report
8	393373	2014.07.15	Kongsberg Maritime/Norway	RoLAN Radar Functionality, Type Approval performance test report
9	DANAK-19/12398 Rev.1	2012.10.05	DELTA/Denmark	Report: Delta, Environmental test report for Radar Interface Network (RIN)
10	328811/P	2010.03.05	Kongsberg Maritime/Norway	K-Bridge Radar test procedure
11	QinetiQ/MS/EES /TSTR0801808/1	2008.08.29	QinetiQ/UK	Report: QinetiQ, Environmental test report for 65925 X Band turning unit
12		2009.11.20	Prediktor /Norway	Radar Target Tracking
13	QINETIQ/MS/EES /TSTR0801152/ 1.1	2008.07.08	QinetiQ/UK	Performance Compliance Testing
14	QINETIQ/D&TS /S ES/TC0609653 Issue 1.0	2006.07.24	QinetiQ/UK	Certificate of Test, 30 kW Turning Unit and Scanner Control Unit
15	QINETIQ/S&E/SP S/CR050588/1.0	2005.04.08	QinetiQ/UK	BME in FST Pedestal
16	QINETIQ/FST/C M T/TR022173	2002.03.21	QinetiQ/UK	Unwanted Emissions Measurements of a Litton Marine X Band Navigation Radar- LM(X)001, LM(X)002, LM(X)003
17	KLM1.00.0061 Rev A	2002.01.09	Kongsberg Fimas /Norway	Environmental Test Report, Verification Test on AIM Safe System
18	DERA/SS/CI/R/T T-20/98/1.1	1999.06.16	DERA /UK	Type testing of Bridgemaster E Series Radar Equipment
19	DERA/SSWI/R/TT -12/97/1.0	1997.10.28	DERA /UK	Type testing of Bridgemaster II Series S-Band

No.	Report No.	Report date	Lab./Test Address	Note
20	DERA/SSWI/R/TT -12/97/1.0	1997.10.28	DERA /UK	Extracted page from report DERA/SSWI/R/TT-12/97
21	DERA/SS/WI/R/T T-22/97/1.0	1997.10.28	DERA /UK	Page 2 of Appendix B from DERA/SS/WI/R/TT-22/97
22	110-0072553-A	2023.04.01	Kongsberg Maritime, Norway	Solid-State JRC X-Band Radar Transceiver Type Approval Test Report
23	462697-A	2020.05.18	Kongsberg Maritime, Norway	JRC Radar Transceiver Type Approval System Test Description
24	462698-C	2021.08.12	Kongsberg Maritime, Norway	JRC Radar Transceiver Type Approval System Test Report
25	476824	2021.03.16	Kongsberg Maritime, Norway	Radar - High Speed Craft Type Approval System Test Report

3.Kongsberg Maritime Radar Manuals

No.	Document Id.	Rev.	Description
1	430413	В	Installation manual: Kongsberg Maritime, S-band Scanner Assembly, Up mast
2	421510	С	Installation Manual: Kongsberg Maritime, X-band Radar Scanner Unit
3	331489	A	Manual: Kongsberg Maritime, Guidelines for the installation of shipborne radar equipment
4	110-0054820D	D	K-Bridge Radar Operator Manual
5	463736/F	F	KM Marine Radar Scanner Installation Manual
6	463763	F	Maintenance Manual:Kongsberg Maritime Radar Scanner
7	470318	В	Maintenance Manual:RIN JRC 230 VAC IP66
8	470337	D	Installation Manual RIN JRC 230 VAC IP66