



Material, sensor pipe: AISI304
 Material, comp cable: PFA -60 - 260°C
 Protection grade: IP67
 Weight (MB744S200K15): 150 gram

ORDERING EXAMPLE: MB744S200K15

Mechanical design _____
 Single element (LETTER NO.1) _____
 L=200 mm _____
 Element type (LETTER NO.2) _____
 CL= 15 decimeter _____

| LETTER No.1 | EXPLANATION |
|-------------|----------------|
| D | Double element |
| S | Single element |

| LETTER No.2 | ELEMENT | RANGE |
|-------------|-----------|----------|
| J | Fe-CuNi | 0-600 °C |
| K | NiCr-NiAl | 0-800 °C |

| | | | |
|--------------------|--------------------|----------|--------------------------|
| Date 1991-02-25 | Dsgn/Dwn AJK/ES | Trac | Scale/Format 1:1 [A4] |
| Checked | Spec Ctrl. | Approved | |

Kongsberg Maritime AS
 Automation
 Trondheim

Temperature sensor type MB744--

DIMENSIONAL SKETCH

| | | |
|-------------------|----------|------------|
| Repl. for | Repl. by | Next sheet |
| Dwg no. MB-744 | Sh.no. | Rev. Lang. |

Description Date/Sign.

Rev.

Description Date/Sign.

Rev.